



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 5/3/05

DAP® Stucco Patch – Dry Mix

- Durable and permanent
- Textured
- Easy to tool and paint

Company Identification:

Manufacturer: DAP Inc.
 Marketed by: DAP Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland 21224
 Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.
 Order Information: 800-327-3339
 Fax Number: 410-534-2650
 Also, visit the DAP website at www.dap.com.

Product Description:

DAP® Stucco Patch may be used to repair large holes and cracks in interior and exterior stucco surfaces. Its easy-to-mix formula blends naturally with existing stucco for a professional finish.

Suggested Uses

Ideal for patching large holes and cracks in stucco surfaces.

Surface Preparation & Application

- Surface must be clean, dry and free of loose paint, plaster, wax, dust and dirt.
- Add stucco patch to clear water in clean container mixing 4 parts of powder to 1 part of water by volume. Stir to a smooth consistency. Let the mixture set for 15 minutes then restir until smooth. Do not mix more material than can be used in 1 to 2 hours. Discard any material that has begun to harden.
- Apply stucco patch with a clean putty knife or trowel. For fills over 1/4” deep apply 2 or more layers allowing each layer to dry before applying the next layer. Use a rubber float to blend patch with the existing stucco surface.

NOTE: Consult paint manufacturer’s recommendations before decorating.

Physical & Chemical Characteristics:

Working Time: 1 to 2 hours
 Setting Time: 2 to 4 hours
 Final Cure: 3 days

Packaging:	<u>UPC</u>	<u>Size</u>	<u>Container</u>	<u>Color</u>
	10510	6.5 lb.	Box	White
	10502	25 lb.	Bag	White

Mixing Ratios
& Coverage:

<u>Stucco Patch</u>	<u>Water</u>	<u>Coverage</u>
6.5 lb.	1 pt.	2 -3 sq. ft. with _" thickness
25 lb.	5 pt.	10-12 sq. ft. with _" thickness

MSDS No.: 00071151001

NOTE: These figures are approximate and may vary with job site conditions.

Clean Up:

Wash skin and hands with soap and water. Cured material must be scraped or sanded away.

Safety:

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at www.dap.com or by calling 888-DAP-TIPS.

Warranty Information:

If you are not satisfied with this product's performance when used as directed, return used container and sales receipt to DAP Inc., Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.