



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224

Phone: 410-675-2100 or 800-543-3840

Revised: 10-09-06

DAP® Strong Stik™ Instant Grab Adhesive

- Gluing Made Powerful
- Holds Projects In Place Instantly
- No Bracing Required
- Multi-Surface Usage
- Indoor/ Outdoor

Packaging: 5.5 fl. oz. Squeeze tube (162 mL)

Color: White

UPC No: 7079801310

Company Identification:

Manufacturer: DAP Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST

Order Information: 800-327-3339

Also, visit the DAP website at www.dap.com.

Product Description:

DAP® Strong Stik™ Instant Grab Adhesive is an instant-grab adhesive ideal for bonding a wide variety of materials. It is perfect for quick and easy repairs. The latex-based formula is low odor and wet adhesive cleans up easily with soap and water. Interior/exterior use.

Suggested Uses:

Bonds:

- Brick
- Concrete
- Tile
- Wood
- Plaster
- Ceramic
- Vinyl
- Masonry
- Glass
- Aluminum
- Metal

Note: Does not bond mirrors.

One surface must be porous.

For Best Results:

- Apply in temperatures 50°F and above
- Keep adhesive at or above 50°F prior to use for easier application.
- Store away from extreme heat or cold.

- Not for continuous water submersion.

Surface Preparation & Application:

1. Surfaces must be clean, dry, structurally sound and free of loose material.
2. Precut and fit materials before applying adhesive.
3. For initial use, unscrew cap, remove foil tab, and replace cap. Flip cap open.
4. Evenly apply bead to surface. For square or rectangle surfaces, use perimeter and “X” bead. For long surfaces, use zigzag bead.
5. Position and press substrates firmly into place.
6. Allow to dry for 24 hours.
7. Flip cap down for re-use. Store away from extreme heat or cold.

Guideline for Usage:

DAP® Strong Stik™ Instant Grab Adhesive was applied to one side of a brick, and then immediately adhered to unfinished drywall. Results show that the amount of adhesive used does affect strength of bond between surfaces.

Surfaces: Brick and Unfinished Drywall		
Brick dimension	Brick weight	Amount of adhesive used
3-3/4" x 3-3/4" x 2-1/4"	2.4 lbs	20 g
7-1/2" x 3-3/4" x 2-1/4"	5 lbs	50 g

Physical & Chemical Characteristics:

Base: Acrylic latex resin
 Volatile: Water
 Flash Point: Greater than 200°F
 Solids: 63% by weight
 Weight/gallon: 10.9 lbs.
 Odor: Mild
 Color: White
 Consistency: Smooth paste
 Application Temperature Range: 50°F to 100°F
 Service Temperature Range: 0°F to 120°F
 Repositioning time: 15 minutes
 Freeze/thaw Stability: 5 cycles
 Shelf Life: 1 year
 MSDS Number: 000 79983 001

Clean Up & Storage:

Use warm, soapy water to clean up excess wet adhesive from surface, hands and tools. Cured adhesive must be cut or scraped away.

Safety:

See product label and Material Safety Data Sheet for safety information. You can request an MSD Sheet by visiting our website at www.dap.com or calling 888-DAP-TIPS.

Satisfaction Guaranteed:

If not satisfied with product's performance when used as directed, return used container and sales receipt to DAP Inc., Technical Customer Service, 2400 Boston St., Baltimore, MD, 21224, for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.

