



# Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224

Phone: 410-675-2100 or 800-543-3840

Revised: 1/30/2007

## DAP® PRESTO PATCH® Ready-Mix Multi-Purpose Patching Compound

- Fill, level or patch cracks and holes in: concrete, plaster, masonry surfaces, wallboard & wood
- Interior/exterior use

**Packaging:** 1 Gallon (3.78 L), 2 Gallons (7.57 L)  
**Color:** White  
**UPC Numbers:** 70798 58555, 58556

### Company Identification:

**Manufacturer:** DAP Inc., 2400 Boston Street, Baltimore, Maryland 21224  
**Usage Information:** DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.  
**Order Information:** 800-327-3339  
**Fax Number:** 410-534-2650  
Also, visit the DAP website at [www.dap.com](http://www.dap.com).

### Product Description:

**DAP® Ready-Mixed Multi-Purpose Presto Patch®** is an easy-to-use, polymer-fortified, high performance patching compound formulated to fill holes & cracks in multitude of interior & exterior surfaces. The product has a smooth working consistency, dries quickly with minimal shrinkage & sands easily. Once dry, it may be filed, drilled, nailed or painted. Provides an excellent floor underlayment for patching & leveling before installation of floor coverings. Not recommended for areas that collect standing water or receive continuous moisture unless coated with a waterproofing product. Set time is 30-60 minutes.

### Suggested Uses:

Fill, level or patch cracks and holes in:

- Concrete
- Plaster
- Masonry Surfaces
- Wallboard
- Wood

### Surface Preparation & Application:

Make sure surface to be repaired is clean and free of dirt, loose particles & foreign material. Widen cracks to at least ¼" in width. Use sandpaper to dull glossy surfaces before repairing. Stir thoroughly before use. Apply with clean putty knife, pushing product completely into crack or damaged area. For a smoother finish, dip putty knife in water & lightly smooth the surface. For repairs deeper than ¼", apply 2 or more layers, allowing to dry between layers. Presto Patch® Multi-Purpose Patching Compound can be sanded or painted 1 to 5 hours after application, depending on temperature, humidity & depth of fill.

**Physical & Chemical Characteristics:**

Consistency:	Heavy bodied paste
Vehicle:	Latex Emulsion
Volatile:	Water
Filler:	Various Inerts
Odor:	Mild
Weight per Gallon:	15.84 lbs
Solids:	78%
Temperature Application Range:	50°F Minimum
Temperature Service Range:	-20°F to 120°F
Shelf Life:	1 Year
Freezing:	Protect from freezing
Drying Time:	1 to 5 hours depending on temperature, relative humidity and depth of fill.
Painting:	1 to 5 hours depending on temperature, relative humidity and depth of fill.
Coverage:	1 gallon will cover approximately 12 sq. ft. at 1/8" thickness.
MSDS:	000 79900 4001

**Clean Up & Storage:**

Wash tools immediately with water. Close tightly after each use. Store in a cool, dry place. Protect from freezing.

**Safety:**

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at [www.dap.com](http://www.dap.com) or by calling 888-DAP-TIPS.

**Satisfaction Guaranteed:**

If you are not satisfied with this product's performance when used as directed, return used container & sales receipt to Technical Customer Service, 2400 Boston Street, Baltimore, MD 21224 for product replacement or sales price refund. Manufacturer will not be liable for incidental or consequential damages.